



A Durability Study of High-temperature PEMFC. Effects of Operating Parameters and Thermal Curing

Jensen, Jens Oluf; Søndergaard, Tonny; Aili, David; Steenberg, Thomas; Hjuler, Hans Aage; Becker, Hans; Zhong, Lijie; Li, Qingfeng

Publication date:
2017

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Jensen, J. O., Søndergaard, T., Aili, D., Steenberg, T., Hjuler, H. A., Becker, H., Zhong, L., & Li, Q. (2017). *A Durability Study of High-temperature PEMFC. Effects of Operating Parameters and Thermal Curing*. Abstract from 5th International CARISMA Conference (2017), Newcastle, United Kingdom.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

A Durability Study of High-temperature PEMFC. Effects of Operating Parameters and Thermal Curing

Jens Oluf Jensen¹, Tonny S ndergaard¹, David Aili¹, Lars N. Cleemann¹, Thomas Steenberg²,
Hans Aage Hjuler², Hans Becker¹, Lijie Zhong¹ and Qingfeng Li¹

¹Department of Energy Conversion and Storage, Kemitorvet 207,
Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark

²Danish Power Systems Ltd., Egeskovvej 6C, DK-3490 Kvistg rd, Denmark

jojen@dtu.dk

Several groups have demonstrated lifetimes of 10.000-20.000 hours for high-temperature PEM fuel cell based on phosphoric acid doped polybenzimidazole (PBI). Nevertheless, durability is still a critical issue that deserves attention. [1]

In the present study, a large number of cells manufactured by Danish Power Systems were tested with hydrogen and air in multichannel test rigs over several years. The operating parameters, temperature, gas flow rates and current load, were varied between 160 and 200  C, stoichiometry up to about 10 (to mimic an air cooled cell) and current densities between 200 and 800 mA cm⁻², respectively. The cells were repeatedly characterized by polarization curves and/or electrochemical impedance spectroscopy. Post mortem analyses were performed by means of microscopy of cross sections, X-ray diffraction for platinum particle size and acid titration of cutout samples of the cells. The usual degradation effects were observed (catalyst particle growth, membrane thinning and acid loss), including the trend of increasing decay rate with increasing temperature or current load. Additionally, a similar correlation with gas flow rate was seen. The long-term degradation was explained as being mainly an effect of acid loss.

In another series of experiments, accelerated stress tests in the form of potential cycling were carried out. Then a decisive effect of humidification was seen. Potential cycling under un-humidified nitrogen resulted in an apparent degradation, which was reversed almost completely after a period of normal operation with air and hydrogen.

Finally, a cell with thermally cured PBI [2] was operated under constant current with a decay rate as low as 0.5  V h⁻¹ for several thousands of hours. [3]

- [1] M. T. D. Jakobsen, J. O. Jensen, L. N. Cleemann and Q. Li. Chapter 22. Durability Issues and Status of PBI Based Fuel Cells. In Q. Li, D. Aili, H. A. Hjuler and J. O. Jensen (eds). High Temperature Polymer Electrolyte Membrane Fuel Cells- Approaches, Status and Perspectives. Springer-Verlag 2016
- [2] D. Aili, L. N. Cleemann, Q. Li, J. O. Jensen, E. Christensen and N. J. Bjerrum. Thermal curing of PBI membranes for high temperature PEM fuel cells. *J. Mater. Chem.* **22** 5444-5453 (2012)
- [3] T. S ndergaard, L. N. Cleemann, H. Becker, D. Aili, T. Steenberg, H. A. Hjuler, L. Seerup, Q. Li and J. O. Jensen. Long-term Durability of HT-PEM Fuel Cells Based on Thermally Cross-linked Polybenzimidazole. *J. Power Sources* **342** 570-578 (2017)